

Titled Panelbox



Titled Panelbox {gu-block} [Documentation](#)  

Display the included content as a configurable block container

formatting

Parameter

Name	Description	Type	This is a required field	Default	Values
Title of the box <code>title</code>		string	✗		
Width <code>width</code>	Restrict the width of the container block. Example: <i>150px</i>	string	✗		
Height <code>height</code>	Restrict the height of the container block. Example: <i>200px</i>	string	✗		
Show header icon <code>headerIconShow</code>		boolean	✗	false	
Header icon <code>headerIcon</code>		string	✗		
Header attachment icon <code>headerIconUrl</code>	Any valid image url can be used. Used when parameter "Header icon" is not defined.	string	✗		
Header icon CSS class <code>headerIconClass</code>	Sets the class attribute of the element for styling or extended functionality. If you add the css class <i>bv-create-button</i> the create content dialog opens on click.	string	✗		
Show header button <code>headerButtonShow</code>		boolean	✗	false	
Header button link <code>headerButtonLink</code>		string	✗		
Internationalization i18n key for the header button text <code>headerButtonText</code>	Any available i18n key can be used.	string	✗		
Header button icon <code>headerButtonIconFont</code>		string	✗		
Header button attachment icon <code>headerButtonIconAttachment</code>	Any valid image url can be used. Used when parameter "Header button icon" is not defined.	string	✗		
Header button link or button <code>headerButtonStyle</code>		enum	✓	button	button, primary_button, primary_button_inverse, link
Header button CSS class <code>headerButtonClass</code>	Sets the class attribute of the element for styling or extended functionality. If you add the css class <i>bv-create-button</i> the create content dialog opens on click.	string	✗		
Show footer button <code>footerButtonShow</code>		boolean	✗	false	
Footer button link <code>footerButtonLink</code>		string	✗		

Internationalization i18n key for the footer button text <code>footerButtonText</code>	Any available i18n key can be used.	string	✗		
Footer button icon <code>footerButtonIconFont</code>		string	✗		
Footer button icon attachment <code>footerButtonIconAttachment</code>	Any valid image url can be used. Used when parameter "Footer button icon" is not defined.	string	✗		
Footer button link or button style <code>footerButtonStyle</code>		enum	✓	button	button, primary_button, primary_button_inverse, link
Footer button CSS class <code>footerButtonClass</code>	Sets the class attribute of the element for styling or extended functionality. If you add the css class <i>bv-create-button</i> the create content dialog opens on click.	string	✗		
The color of the header (title) text <code>color_header_font</code>		string	✗		
The background color of the header element <code>color_header_background</code>		string	✗		
The background color of the content <code>color_content_background</code>		string	✗		
The color of the border <code>color_border</code>		string	✗		
Link text color <code>color_links</code>		string	✗		
Internationalization i18n key for the title <code>i18n</code>	Any available i18n key can be used.	string	✗		
Content CSS class <code>contentCssClass</code>	A CSS class that is added to the div element content container	string	✗		
Block CSS class <code>quBlockCssClass</code>	A CSS class that is added to the wrapping blockelement div container	string	✗		
Adds an element that clears floating <code>showBr</code>	If true, a line-break element with "clear float" declaration is rendered. This helps if some content is floating, e.g. buttons	boolean	✗	false	
Show the header <code>showHeader</code>		boolean	✗	true	
Hide empty body <code>hideEmptyBody</code>	Hides the complete block if the content is empty. Attention: a block is only empty if there is no html inside. An empty div element isnt empty!	boolean	✗	true	
Min/Max button <code>true false minimize_button</code>	Show a minimize/maximize button in the header	boolean	✗	true	
Minimized <code>minimize</code>	The panel is minimized by default	boolean	✗	false	
Content padding <code>css_blockelement_border</code>	The padding value of the content container (all sides). Padding is within the element. Example: <i>10px</i>	string	✗		
Content type <code>contentType</code>	A predefined set of content representation. Example: if the child content is a link list, its possible to render a nice list display with separating lines.	enum	✗	normal	normal, linkListNormal, linkListDotted

Examples

This helps, if some content ist floating, e.g. buttons